

CHILLER SELECTION REPORT

Daikin Refrigeration Malaysia Sdn. Bhd.

Project : Project Name CST
Created By : Cheong ST

Customer Input

Selected Model / Type : UAM80C3F / Fixed Speed Scroll Chiller Version C
Ambient Temperature : 35.0 °C Frequency : 50 Hz
Chilled Water : EWT 11.00 °C Voltage : 380-415 V
LWT 6.00 °C Country of Origin : Malaysia

Generated Outputs

Full Load Performance			Nominal Data (AHRI Standard)		Input Conditions		
Cooling Capacity	:		80.00		78.16		TR
			281.4		274.9		kW
Current	:	Compressor	161		161		A
		Fan	18		18		A
		Total	179		179		A
Power Input	:	Compressor	92.20		92.10		kW
		Fan	12.00		12.00		kW
		Total	104.2		104.1		kW
COP	:		2.700		2.641		kW/kW
Flow Rate	:		48.45		47.34		m³/h
Pressure Drop	:		37.4		36.1		kPa

- Nominal data is based on the AHRI (551/591) standard condition of EWT/LWT of 12.00/7.00°C, and ambient temperature of 35.0°C.
- Input Condition data is based on customer's input condition of EWT/LWT, and ambient temperature.
- Evaporator rating fouling factor = 0.018 m²/kW, and rating altitude at 0 m.

Part Load Performance

IPLV		3.926										kW/kW
Point		1	2	3	4	5	6	7	8	9	10	
Corresponding Capacity		100.0	77.6	72.4	55.2	50.0	44.8	27.6	22.4	-	-	%
Total Cooling Capacity		78.16	60.66	56.58	43.16	39.08	35.00	21.58	17.50	-	-	TR
Total Cooling Capacity		274.9	213.4	199.0	151.8	137.5	123.1	75.90	61.55	-	-	kW
Total Power Input		104.1	81.68	76.47	59.26	52.05	48.84	29.63	24.42	-	-	kW
Total Current		179	141	131	102	90	83	51	42	-	-	A
COP		2.641	2.612	2.602	2.562	2.641	2.520	2.562	2.520	-	-	kW/kW
Ambient Temperature		35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	-	-	°C
EEWT		11.00	9.88	9.62	8.76	8.50	8.24	7.38	7.12	-	-	°C
ELWT		6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00	-	-	°C
Flow Rate		47.34	47.34	47.34	47.34	47.34	47.34	47.34	47.34	-	-	m ³ /h
Pressure Drop		36.1	36.1	36.1	36.1	36.1	36.1	36.1	36.1	-	-	kPa

Others

MCA		223										A
No. of Refrigerant Circuit		2										-
Refrigerant Type		R410A										-
Refrigerant Charge	System 1/2	25.0 / 25.0										kg/System
Chiller Dimension	W / D / H	2237 / 3263 / 2156										mm
Weight	Shipping	2917										kg
	Operating	3039										kg

Evaporator

Type		S&T										-
Inlet/Outlet Diameter		5" Victaulic Joint										-
Flow Rate	Min / Max	15.00 / 56.70										m ³ /h
Pressure Drop	Min / Max	5.00 / 47.0										kPa

Compressor

Quantity	System 1/2	2 / 2										-
Type		Hermetic-sealed (Scroll)										-
Oil Charge	System 1/2	13.4 / 13.4										L/System

Condenser

Coil												-
Tube	Type	Copper										-
Fin	Type	Aluminium										-
Surface Area/ Coil		11.52										m ² /Coil
Fan												-
Type/ Drive		Axial / Direct										-
Quantity per System		3										-

Certified in accordance with the AHRI Air-Cooled Water-Chilling Packages Certification Program, which is based on AHRI Standard 550/590 (I-P) and AHRI Standard 551/591 (SI). Certified Units may be found in the AHRI Directory at www.ahridirectory.org



Note : For any enquiry, please contact your authorized sales agent.

CSQS.C01.S01

09-Dec, 2022 15:04

Page : 1/2