

CHILLER SELECTION REPORT

Daikin Refrigeration Malaysia Sdn. Bhd.

Project : CSS Dec 09
Created By : lee ming yang

Customer Input

Selected Model / Type : UAM80C3F / Fixed Speed Scroll Chiller Version C
Ambient Temperature : 33.0 °C Frequency : 50 Hz
Chilled Water : EWT 12.00 °C Voltage : 380-415 V
LWT 6.00 °C Country of Origin : Malaysia

Generated Outputs

Full Load Performance		Nominal Data (AHRI Standard)				Input Conditions			
Cooling Capacity	:		80.00			80.00			TR
			281.4			281.4			kW
Current	:	Compressor	161			156			A
		Fan	18			18			A
		Total	179			174			A
Power Input	:	Compressor	92.20			88.51			kW
		Fan	12.00			12.00			kW
		Total	104.2			100.5			kW
COP	:		2.700			2.799			kW/kW
Flow Rate	:		48.45			40.38			m ³ /h
Pressure Drop	:		37.4			28.4			kPa

- Nominal data is based on the AHRI (551/591) standard condition of EWT/LWT of 12.00/7.00°C, and ambient temperature of 35.0°C.
- Input Condition data is based on customer's input condition of EWT/LWT, and ambient temperature.
- Evaporator rating fouling factor = 0.018 m².K/kW, and rating altitude at 0 m.

Part Load Performance

IPLV	:	3.926										kW/kW
Point	:	1	2	3	4	5	6	7	8	9	10	
Corresponding Capacity	:	100.0	78.1	72.9	55.6	50.3	45.1	27.8	22.5	-	-	%
Total Cooling Capacity	:	80.00	62.50	58.30	44.47	40.27	36.07	22.23	18.03	-	-	TR
Total Cooling Capacity	:	281.4	219.8	205.0	156.4	141.6	126.8	78.19	63.42	-	-	kW
Total Power Input	:	100.5	78.90	73.86	57.29	50.25	47.22	28.65	23.61	-	-	kW
Total Current	:	174	137	128	100	87	81	50	41	-	-	A
COP	:	2.799	2.786	2.776	2.730	2.818	2.686	2.730	2.686	-	-	kW/kW
Ambient Temperature	:	33.0	33.0	33.0	33.0	33.0	33.0	33.0	33.0	-	-	°C
EEWT	:	12.00	10.69	10.37	9.33	9.02	8.70	7.67	7.35	-	-	°C
ELWT	:	6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00	-	-	°C
Flow Rate	:	40.38	40.38	40.38	40.38	40.38	40.38	40.38	40.38	-	-	m ³ /h
Pressure Drop	:	28.4	28.4	28.4	28.4	28.4	28.4	28.4	28.4	-	-	kPa

Others

MCA	:	223										A
No. of Refrigerant Circuit	:	2										-
Refrigerant Type	:	R410A										-
Refrigerant Charge	:	System 1/2	25.0 / 25.0									kg/System
Chiller Dimension	:	W / D / H	2237 / 3263 / 2156									mm
Weight	:	Shipping	2917									kg
	:	Operating	3039									kg

Evaporator

Type	:	S&T										-
Inlet/Outlet Diameter	:	5" Victaulic Joint										-
Flow Rate	:	Min / Max	15.00 / 56.70									m ³ /h
Pressure Drop	:	Min / Max	5.00 / 47.0									kPa

Compressor

Quantity	:	System 1/2	2 / 2										-
Type	:		Hermetic-sealed (Scroll)										-
Oil Charge	:	System 1/2	13.4 / 13.4										L/System

Condenser

Coil				
Tube	:	Type	Copper	-
Fin	:	Type	Aluminium	-
Surface Area/ Coil	:		11.52	m²/Coil
Fan				
Type/ Drive	:		Axial / Direct	-
Quantity per System	:		3	-

Certified in accordance with the AHRI Air-Cooled Water-Chilling Packages Certification Program, which is based on AHRI Standard 550/590 (I-P) and AHRI Standard 551/591 (SI). Certified Units may be found in the AHRI Directory at www.ahridirectory.org



Note : For any enquiry, please contact your authorized sales agent.

CSQS.C01.S01

09-Dec, 2022 15:35

Page : 1/2