

CHILLER SELECTION REPORT

Daikin Refrigeration Malaysia Sdn. Bhd.

Project : Project Name CST
Created By : Cheong ST

Customer Input

Selected Model / Type : UAM80C3F / Fixed Speed Scroll Chiller Version C
Ambient Temperature : 35.0 °C Frequency : 50 Hz
Chilled Water : EWT 11.00 °C Voltage : 380-415 V
LWT 6.00 °C Country of Origin : Malaysia

Generated Outputs

Full Load Performance		Nominal Data (AHRI Standard)		Input Conditions	
Cooling Capacity	:		80.00	78.16	TR
			281.4	274.9	kW
Current	:	Compressor	161	161	A
		Fan	18	18	A
		Total	179	179	A
Power Input	:	Compressor	92.20	92.10	kW
		Fan	12.00	12.00	kW
		Total	104.2	104.1	kW
COP	:		2.700	2.641	kW/kW
Flow Rate	:		48.45	47.34	m ³ /h
Pressure Drop	:		37.4	36.1	kPa

Note : 1. Nominal data is based on the AHRI (551/591) standard condition of EWT/LWT of 12.00/7.00°C, and ambient temperature of 35.0°C.
2. Input Condition data is based on customer's input condition of EWT/LWT, and ambient temperature.
3. Evaporator rating fouling factor = 0.018 m².K/kW, and rating altitude at 0 m.

Part Load Performance

IPLV	:	3.926										kW/kW
Point	:	1	2	3	4	5	6	7	8	9	10	
Corresponding Capacity	:	100.0	77.6	72.4	55.2	50.0	44.8	27.6	22.4	-	-	%
Total Cooling Capacity	:	78.16	60.66	56.58	43.16	39.08	35.00	21.58	17.50	-	-	TR
Total Cooling Capacity	:	274.9	213.4	199.0	151.8	137.5	123.1	75.90	61.55	-	-	kW
Total Power Input	:	104.1	81.68	76.47	59.26	52.05	48.84	29.63	24.42	-	-	kW
Total Current	:	179	141	131	102	90	83	51	42	-	-	A
COP	:	2.641	2.612	2.602	2.562	2.641	2.520	2.562	2.520	-	-	kW/kW
Ambient Temperature	:	35.0	35.0	35.0	35.0	35.0	35.0	35.0	35.0	-	-	°C
EEWT	:	11.00	9.88	9.62	8.76	8.50	8.24	7.38	7.12	-	-	°C
ELWT	:	6.00	6.00	6.00	6.00	6.00	6.00	6.00	6.00	-	-	°C
Flow Rate	:	47.34	47.34	47.34	47.34	47.34	47.34	47.34	47.34	-	-	m³/h
Pressure Drop	:	36.1	36.1	36.1	36.1	36.1	36.1	36.1	36.1	-	-	kPa

Others

MCA	:	223	A
No. of Refrigerant Circuit	:	2	-
Refrigerant Type	:	R410A	-
Refrigerant Charge	: System 1/2	25.0 / 25.0	kg/System
Chiller Dimension	: W / D / H	2237 / 3263 / 2156	mm
Weight	: Shipping	2917	kg
	: Operating	3039	kg

Evaporator

Type	:	S&T	-
Inlet/Outlet Diameter	:	5" Victaulic Joint	-
Flow Rate	: Min / Max	15.00 / 56.70	m ³ /h
Pressure Drop	: Min / Max	5.00 / 47.0	kPa

Compressor

Quantity	: System 1/2	2 / 2	-
Type	:	Hermetic-sealed (Scroll)	-
Oil Charge	: System 1/2	13.4 / 13.4	L/System

Condenser

Coil	:		-
Tube	: Type	Copper	-
Fin	: Type	Aluminium	-
Surface Area/ Coil	:	11.52	m ² /Coil
Fan	:		-
Type/ Drive	:	Axial / Direct	-
Quantity per System	:	3	-

Certified in accordance with the AHRI Air-Cooled Water-Chilling Packages Certification Program, which is based on AHRI Standard 550/590 (I-P) and AHRI Standard 551/591 (SI). Certified Units may be found in the AHRI Directory at www.ahridirectory.org



Note : For any enquiry, please contact your authorized sales agent.

CSQS.C01.S01

16-Dec, 2022 11:36

Page : 1/2