

CHILLER SELECTION REPORT

Daikin Refrigeration Malaysia Sdn. Bhd.

Project : Test
Created By : Admin Codetinker

Customer Input

Selected Model / Type : UAM80C3F / Fixed Speed Scroll Chiller Version C
Ambient Temperature : 40.0 °C Frequency : 50 Hz
Chilled Water : EWT 12.00 °C Voltage : 380-415 V
LWT 7.00 °C Country of Origin : Malaysia

Generated Outputs

Full Load Performance		Nominal Data (AHRI Standard)		Input Conditions	
Cooling Capacity	:		80.00	74.60	TR
			281.4	262.4	kW
Current	:	Compressor	161	175	A
		Fan	18	18	A
		Total	179	193	A
Power Input	:	Compressor	92.20	102.2	kW
		Fan	12.00	12.00	kW
		Total	104.2	114.2	kW
COP	:		2.700	2.297	kW/kW
Flow Rate	:		48.45	45.18	m ³ /h
Pressure Drop	:		37.4	33.6	kPa

Note : 1. Nominal data is based on the AHRI (551/591) standard condition of EWT/LWT of 12.00/7.00°C, and ambient temperature of 35.0°C.
2. Input Condition data is based on customer's input condition of EWT/LWT, and ambient temperature.
3. Evaporator rating fouling factor = 0.018 m².K/kW, and rating altitude at 0 m.

Part Load Performance

IPLV	:	3.926										kW/kW
Point	:	1	2	3	4	5	6	7	8	9	10	
Corresponding Capacity	:	100.0	77.6	72.4	55.2	50.0	44.8	27.6	22.4	-	-	%
Total Cooling Capacity	:	74.60	57.90	54.00	41.20	37.30	33.40	20.60	16.70	-	-	TR
Total Cooling Capacity	:	262.4	203.6	189.9	144.9	131.2	117.5	72.45	58.73	-	-	kW
Total Power Input	:	114.2	89.54	83.82	64.84	57.12	53.40	32.42	26.70	-	-	kW
Total Current	:	193	151	141	110	97	90	55	45	-	-	A
COP	:	2.297	2.274	2.266	2.235	2.297	2.200	2.235	2.200	-	-	kW/kW
Ambient Temperature	:	40.0	40.0	40.0	40.0	40.0	40.0	40.0	40.0	-	-	°C
EEWT	:	12.00	10.88	10.62	9.76	9.50	9.24	8.38	8.12	-	-	°C
ELWT	:	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	-	-	°C
Flow Rate	:	45.18	45.18	45.18	45.18	45.18	45.18	45.18	45.18	-	-	m³/h
Pressure Drop	:	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	-	-	kPa

Others

MCA	:	223	A
No. of Refrigerant Circuit	:	2	-
Refrigerant Type	:	R410A	-
Refrigerant Charge	: System 1/2	25.0 / 25.0	kg/System
Chiller Dimension	: W / D / H	2237 / 3263 / 2156	mm
Weight	: Shipping	2917	kg
	: Operating	3039	kg

Evaporator

Type	:	S&T	-
Inlet/Outlet Diameter	:	5" Victaulic Joint	-
Flow Rate	: Min / Max	15.00 / 56.70	m ³ /h
Pressure Drop	: Min / Max	5.00 / 47.0	kPa

Compressor

Quantity	: System 1/2	2 / 2	-
Type	:	Hermetic-sealed (Scroll)	-
Oil Charge	: System 1/2	13.4 / 13.4	L/System

Condenser

Coil	:		-
Tube	: Type	Copper	-
Fin	: Type	Aluminium	-
Surface Area/ Coil	:	11.52	m ² /Coil
Fan	:		-
Type/ Drive	:	Axial / Direct	-
Quantity per System	:	3	-

Certified in accordance with the AHRI Air-Cooled Water-Chilling Packages Certification Program, which is based on AHRI Standard 550/590 (I-P) and AHRI Standard 551/591 (SI). Certified Units may be found in the AHRI Directory at www.ahridirectory.org



Note : For any enquiry, please contact your authorized sales agent.

CSQS.C01.S01

24-Dec, 2022 21:03

Page : 1/2