



CHILLER SELECTION REPORT

Daikin Refrigeration Malaysia Sdn. Bhd.

Project : Lee Ming Yang-R0
Created By : lee ming yang

Customer Input

Selected Model / Type : UAM60CFM / Fixed Speed Scroll Chiller Version C
Ambient Temperature : 35.0 °C Frequency : 50 Hz
Chilled Water : EWT 14.00 °C Voltage : 380-415 V
LWT 9.00 °C Country of Origin : Malaysia

Generated Outputs

Full Load Performance		Nominal Data (AHRI Standard)		Input Conditions	
Cooling Capacity		59.27	63.61	TR	
		208.5	223.7	kW	
Current	Compressor	115	115	A	
	Fan	18	18	A	
	Total	133	133	A	
Power Input	Compressor	67.18	67.26	kW	
	Fan	12.00	12.00	kW	
	Total	79.18	79.26	kW	
COP		2.633	2.822	kW/kW	
Flow Rate		35.90	38.52	m ³ /h	
Pressure Drop		37.9	42.6	kPa	

Note :
1. Nominal data is based on the AHRI (551/591) standard condition of EWT/LWT of 12.00/7.00°C, and ambient temperature of 35.0°C.
2. Input Condition data is based on customer's input condition of EWT/LWT, and ambient temperature.
3. Evaporator rating fouling factor = 0.018 m².K/kW, and rating altitude at 0 m.

Part Load Performance

IPLV		3.850										kW/kW
Point		1	2	3	4	5	6	7	8	9	10	
Corresponding Capacity		100.0	75.0	50.0	25.0	-	-	-	-	-	-	%
Total Cooling Capacity		63.61	47.71	31.80	15.90	-	-	-	-	-	-	TR
Total Cooling Capacity		223.7	167.8	111.9	55.93	-	-	-	-	-	-	kW
Total Power Input		79.26	60.45	39.63	20.82	-	-	-	-	-	-	kW
Total Current		133	102	67	35	-	-	-	-	-	-	A
COP		2.822	2.776	2.822	2.687	-	-	-	-	-	-	kW/kW
Ambient Temperature		35.0	35.0	35.0	35.0	-	-	-	-	-	-	°C
EEWT		14.00	12.75	11.50	10.25	-	-	-	-	-	-	°C
ELWT		9.00	9.00	9.00	9.00	-	-	-	-	-	-	°C
Flow Rate		38.52	38.52	38.52	38.52	-	-	-	-	-	-	m ³ /h
Pressure Drop		42.6	42.6	42.6	42.6	-	-	-	-	-	-	kPa

Others

MCA		164	A
No. of Refrigerant Circuit		2	-
Refrigerant Type		R410A	-
Refrigerant Charge	System 1/2	21.0 / 21.0	kg/System
Chiller Dimension	W / D / H	2237 / 3263 / 2156	mm
Weight	Shipping	2052	kg
	Operating	2174	kg

Evaporator

Type		S&T	-
Inlet/Outlet Diameter		4" Victaulic Joint	-
Flow Rate	Min / Max	13.70 / 61.20	m ³ /h
Pressure Drop	Min / Max	7.00 / 90.0	kPa

Compressor

Quantity	System 1/2	2 / 2	-
Type		Hermetic-sealed (Scroll)	-
Oil Charge	System 1/2	13.4 / 13.4	L/System

Condenser

Coil			
Tube	Type	Copper Tube	-
Fin	Type	Aluminium Fin	-
Surface Area/ Coil		11.52	m ² /Coil
Fan			
Type/ Drive		Axial / Direct	-
Quantity per System		3	-

Note : For any enquiry, please contact your authorized sales agent.

CSQS.C01.S01

06-Apr, 2023 09:50

Page : 1/2