



CHILLER SELECTION REPORT

Daikin Refrigeration Malaysia Sdn. Bhd.

Project : UAM80CUM
Created By : KONG CHU YEE

Customer Input

Selected Model / Type : UAM80CUM / Fixed Speed Scroll Chiller Version B
Ambient Temperature : 35.0 °C Frequency : 60 Hz
Chilled Water : EWT 12.00 °C Voltage : 380 V
LWT 7.00 °C Country of Origin : Malaysia

Generated Outputs

Full Load Performance			Nominal Data (AHRI Standard)		Input Conditions		
Cooling Capacity	:		80.21		80.21		TR
			282.1		282.1		kW
Current	:	Compressor	167		167		A
		Fan	21		21		A
		Total	188		188		A
Power Input	:	Compressor	89.90		89.90		kW
		Fan	9.000		9.000		kW
		Total	98.90		98.90		kW
COP	:		2.852		2.852		kW/kW
Flow Rate	:		48.58		48.58		m³/h
Pressure Drop	:		68.3		68.3		kPa
Note	:	1. Nominal data is based on the AHRI (551/591) standard condition of EWT/LWT of 12.00/7.00°C, and ambient temperature of 35.0°C. 2. Input Condition data is based on customer's input condition of EWT/LWT, and ambient temperature. 3. Evaporator rating fouling factor = 0.018 m².K/kW, and rating altitude at 0 m.					

Part Load Performance

IPLV	:	-										kW/kW
Point	:	1	2	3	3	4	4	-	-	-	-	
Corresponding Capacity	:	100.0	55.6	60.6	40.4	42.6	42.6	-	-	-	-	%
Total Cooling Capacity	:	80.21	44.60	48.61	32.40	34.21	34.21	-	-	-	-	TR
Total Cooling Capacity	:	282.1	156.9	171.0	114.0	120.3	120.3	-	-	-	-	kW
Total Power Input	:	98.90	46.40	38.20	25.47	23.11	23.11	-	-	-	-	kW
Total Current	:	188	94	81	54	52	52	-	-	-	-	A
COP	:	2.852	3.381	4.475	4.475	5.206	5.206	-	-	-	-	kW/kW
Ambient Temperature	:	35.0	27.0	19.0	19.0	13.0	13.0	-	-	-	-	°C
EEWT	:	12.00	9.78	10.03	9.02	9.13	9.13	-	-	-	-	°C
ELWT	:	7.00	7.00	7.00	7.00	7.00	7.00	-	-	-	-	°C
Flow Rate	:	48.58	48.58	48.58	48.58	48.58	48.58	-	-	-	-	m³/h
Pressure Drop	:	68.3	68.3	68.3	68.3	68.3	68.3	-	-	-	-	kPa

Others

MCA		226	A
No. of Refrigerant Circuit		2	-
Refrigerant Type		R410A	-
Refrigerant Charge	System 1/2	25.0 / 25.0	kg/System
Chiller Dimension	W / D / H	2237 / 3263 / 2156	mm
Weight	Shipping	2819	kg
	Operating	2941	kg

Evaporator

Type		S&T	-
Inlet/Outlet Diameter		5" Victaulic Joint	-
Flow Rate	Min / Max	12.60 / 52.30	m ³ /h
Pressure Drop	Min / Max	7.00 / 76.0	kPa

Compressor

Quantity	System 1/2	3 / 3	-
Type		Hermetic-sealed (Scroll)	-
Oil Charge	System 1/2	20.1 / 20.1	L/System

Condenser

Coil			
Tube	Type	Copper Tube	-
Fin	Type	Aluminium Fin	-
Surface Area/ Coil		11.52	m ² /Coil
Fan			
Type/ Drive		Axial / Direct	-
Quantity per System		3	-

Note : For any enquiry, please contact your authorized sales agent.

CSQS.C01.S01

30-Sep, 2024 08:41

Page : 1/2