



CHILLER SELECTION REPORT

Daikin Refrigeration Malaysia Sdn. Bhd.

Project : Lee Ming Yang
Created By : DRMSA Software

Customer Input

Selected Model / Type : UAM60CFM / Fixed Speed Scroll Chiller Version C
Ambient Temperature : 35.0 °C Frequency : 50 Hz
Chilled Water : EWT 12.00 °C Voltage : 380-415 V
LWT 7.00 °C Country of Origin : Malaysia

Generated Outputs

Full Load Performance			Nominal Data (AHRI Standard)		Input Conditions		
Cooling Capacity	:		59.27		59.27		TR
			208.5		208.5		kW
Current	:	Compressor	115		115		A
		Fan	18		18		A
		Total	133		133		A
Power Input	:	Compressor	67.18		67.18		kW
		Fan	12.00		12.00		kW
		Total	79.18		79.18		kW
COP	:		2.633		2.633		kW/kW
Flow Rate	:		35.90		35.90		m³/h
Pressure Drop	:		37.9		37.9		kPa
Note	:	1. Nominal data is based on the AHRI (551/591) standard condition of EWT/LWT of 12.00/7.00°C, and ambient temperature of 35.0°C.					

- Nominal data is based on the AHRI (551/591) standard condition of EWT/LWT of 12.00/7.00°C, and ambient temperature of 35.0°C.
- Input Condition data is based on customer's input condition of EWT/LWT, and ambient temperature.
- Evaporator rating fouling factor = 0.018 m².K/kW, and rating altitude at 0 m.

Part Load Performance

IPLV	:	3.850										kW/kW
Point	:	1	2	2	3	3	4	-	-	-	-	
Corresponding Capacity	:	100.0	83.9	55.9	61.3	30.7	32.5	-	-	-	-	%
Total Cooling Capacity	:	59.27	49.72	33.14	36.34	18.17	19.27	-	-	-	-	TR
Total Cooling Capacity	:	208.5	174.9	116.6	127.8	63.91	67.76	-	-	-	-	kW
Total Power Input	:	79.18	52.47	34.32	29.96	15.98	14.61	-	-	-	-	kW
Total Current	:	133	91	60	55	29	27	-	-	-	-	A
COP	:	2.633	3.332	3.397	4.267	4.000	4.639	-	-	-	-	kW/kW
Ambient Temperature	:	35.0	27.0	27.0	19.0	19.0	13.0	-	-	-	-	°C
EEWT	:	12.00	11.19	9.80	10.07	8.53	8.63	-	-	-	-	°C
ELWT	:	7.00	7.00	7.00	7.00	7.00	7.00	-	-	-	-	°C
Flow Rate	:	35.90	35.90	35.90	35.90	35.90	35.90	-	-	-	-	m³/h
Pressure Drop	:	37.9	37.9	37.9	37.9	37.9	37.9	-	-	-	-	kPa

Others

MCA		164								A
No. of Refrigerant Circuit		2								-
Refrigerant Type		R410A								-
Refrigerant Charge	System 1/2	21.0 / 21.0								kg/System
Chiller Dimension	W / D / H	2237 / 3263 / 2156								mm
Weight	Shipping	2052								kg
	Operating	2174								kg

Evaporator

Type		S&T								-
Inlet/Outlet Diameter		4" Victaulic Joint								-
Flow Rate	Min / Max	13.70 / 61.20								m ³ /h
Pressure Drop	Min / Max	7.00 / 90.0								kPa

Compressor

Quantity	System 1/2	2 / 2								-
Type		Hermetic-sealed (Scroll)								-
Oil Charge	System 1/2	13.4 / 13.4								L/System

Condenser

Coil										-
Tube	Type	Copper Tube								-
Fin	Type	Aluminium Fin								-
Surface Area/ Coil		11.52								m ² /Coil
Fan										-
Type/ Drive		Axial / Direct								-
Quantity per System		3								-

Note : For any enquiry, please contact your authorized sales agent.

CSQS.C01.S01

30-Sep, 2024 14:34

Page : 1/2